CISCO

Switch Cisco Catalyst C9200-24T-E, 24x Gigabit Ethernet RJ45, Network Essentials, Layer 3 Managed, Rackmount 1U - Hiri

SKU: 26030245 · EAN: 0889728168236

SPECIFIKAT TEKNIKE

50 specifikat e produktit

ATRIBUTI	VLERA
Management features	
Switch type	Managed
Switch layer	L3
Feature	Quality of Service (QoS) support
Feature	Web-based management
Feature	Traffic classification
Feature	ARP inspection
Feature	Configuring Location Settings (CLI)
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	48
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Fast Ethernet (copper) ports quantity	48
Power connector	AC-in jack
Network	
Feature	Full duplex
Feature	IP routing
Routing entries	4000
Feature	Flow control support
Feature	Spanning tree protocol
Feature	VLAN support
Number of VLANs	4096
Data transmission	
Feature	Jumbo frames support
Jumbo frames	9198
Packet buffer memory	6 MB

Security	
Feature	Access Control List (ACL)
Security algorithms	128-bit AES
Multicast features	
Feature	Multicast support
Multicast MAC address table	1000 entries
IPv4 multicast entries	4000
IPv6 multicast entries	2000
Protocols	
Management protocols	SNMPv1/v2c/v3
Routing protocols	CDP, EIGRP, OSPF, RIP, VRRP
Design	
Product colour	Grey
Performance	
Memory type	DRAM
Internal memory	4000 MB
Flash memory	4000 MB
Power	
Feature	Power supply included
Feature	Redundant power supply (RPS) support
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Input current	1.6 - 0.7 A
Power consumption (typical)	125 W
Operational conditions	
Operating temperature (T-T)	-5 - 45 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 90%
Operating altitude	0 - 3000 m
Weight & dimensions	
Width	445 mm
Depth	350 mm
Height	44 mm
Weight	5 kg
Packaging data	

Package type	Box
Certificates	
Certification	RoHS, IEC 60950-1, UL 60950-1, CAN/CSA C22.2 No. 60950-1, EN 60950-1, AS/NZS 60950.1
Logistics data	
Harmonized System (HS) code	85176990