TELTONIKA

Ruter Industrial Teltonika TRB501, 5G Sub-6 GHz, 4G LTE Cat 19, 3G, 2.5GbE - Zezë

SKU: 26027375 · EAN: 4779051849215

SPECIFIKAT TEKNIKE

21 specifikat e produktit

ATRIBUTI	VLERA
Performance	
Mobile standard	5G Sub-6 GHz SA/NSA, 3GPP Release 16
Download speed	up to 3.4 Gbps (5G) / up to 1.6 Gbps (4G LTE CAT 19)
Upload speed	up to 900 Mbps (5G)
Processor	
CPU	Qualcomm, 1.5 GHz
Memory	
RAM	512 MB GB
Storage	
Flash storage	512 MB
Software	
Operating system	RutOS (OpenWrt Linux)
Ports & interfaces	
Ethernet	1 x RJ45, 10/100/1000/2500 Mbps
USB	1 x Micro-USB
Antenna connectors	4 x SMA female
I/O	2 x configurable I/O
SIM	1 x Mini-SIM (2FF)
Network	
Protocols	Modbus, DNP3, DLMS, MQTT, SNMP, SSH, OpenVPN, IPSec
Management features	
Remote management	Teltonika RMS, WebUI, FOTA, TR-069
Design	
Housing	anodized aluminum
Protection rating	IP30
Weight & dimensions	

Dimensions	100 x 30 x 93.4 mm
Weight	241 g
Power	
Power input	9-30 VDC
Power over Ethernet (PoE)	
PoE	passive PoE (via Ethernet port)
Operational conditions	
Operating temperature	-40°C to +75°C