AXIS

Set Kamerash Sigurie AXIS P3905-R Mk III, 10 Kamera, 2MP, 1920x1080, 2.8mm, M12, PoE, IP66, IP67, IK10 - Bardhë

SKU: 26025592 · EAN: 7331021089433

SPECIFIKAT TEKNIKE

71 specifikat e produktit

ATRIBUTI	VLERA
Performance	
Type	IP security camera
Placement supported	Indoor
Connectivity technology	Wired
Feature	PTZ control
PTZ modes	Digital PTZ
Feature	Tour recording
Feature	Preset points
Feature	Wide Dynamic Range (WDR)
Design	
Form factor	Dome
Mounting type	Ceiling
Product colour	Black, White
Housing material	Aluminium
International Protection (IP) code	IP66, IP67
IK code	IK10
Camera	
Minimum illumination	0.02 lx
Angle of rotation	350°
Lens viewing angle. horizontal	107°
Lens viewing angle. vertical	56°
Tilt angle range	15 - 90°
Pan range	-30 - 30°
Camera pixel size	2.8 µm
Camera shutter speed	1/19000 - 1/5 s
Number of Privacy masking areas	32

Image sensor	
Number of sensors	1
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")
Sensor type	CMOS
Lens system	
Number of lenses	1
Detect distance	21.1 m
Observe distance	7.4 m
Recognize distance	4.2 m
Maximum aperture number	1.2
Identify distance	2.1 m
Fixed focal length	2.8 mm
Closest focusing distance	0.3 m
Video	
Maximum resolution	1920 x 1080 pixels
Total megapixels	2 MP
Video formats supported	H.264, H.265, M-JPEG
Supported graphics resolutions	320 x 240, 640 x 360, 640 x 400, 1280 x 800, 1280 x 960, 1920 x 1080 (HD 1080)
Frame rate	30 fps
Feature	Video streaming
Feature	Noise reduction
Noise reduction technology	2D noise reduction, 3D noise reduction
Image quality adjustment	Brightness, Contrast, Sharpness
Feature	Privacy masking
Bit rate control	Variable Bit Rate (VBR)
Network	
Networking standards	IEEE 802.1AE, IEEE 802.1x, IEEE 802.3af, IEEE 802.3at
Streaming method	Multicast
Storage	
Feature	Card reader integrated
Compatible memory cards	MicroSD (TransFlash), MicroSDHC, MicroSDXC
Flash memory	512 MB
Internal memory	1024 MB
Security	
Feature	Password protection

Feature	Video motion detection
Security algorithms	256-bit AES-XTS, EAP-TLS, HTTPS, MSCHAPv2, PEAP
Alert notification type	E-mail
Feature	Pixel counter
Feature	Digest authentication
Power	
Power source type	PoE
Power consumption (typical)	2.2 W
Power consumption (max)	3.8 W
Operational conditions	
Operating temperature (T-T)	-30 - 55 °C
Storage temperature (T-T)	-40 - 65 °C
Operating relative humidity (H-H)	10 - 100%
Weight & dimensions	
Width	110 mm
Depth	110 mm
Height	50 mm
Weight	241 g
Sustainability	
Compliance certificates	REACH, RoHS
Packaging content	
Number of cameras	10
Feature	Manual
Other features	
Doesn't contain	CFR, PVC/BFR