NETGEAR

Switch NETGEAR M4350-16M4V (MSM4320), 16 porta 2.5G PoE++, 4 porta SFP28 25G, PoE 530W, deri në 1130W, Managed Layer 3, Rack 1U - Zezë

SKU: 26031018 · EAN: 0606449175073

SPECIFIKAT TEKNIKE

37 specifikat e produktit

ATRIBUTI	VLERA
Design	
Form factor	Rack-mountable, 1U
Color	Black
Ports & interfaces	
Total ports	20 (16x 2.5G PoE++, 4x 25G SFP28)
Front ports	8x 2.5G PoE++ Neutrik etherCON (RJ45)
Rear ports	8x 2.5G PoE++ standard RJ45
Uplink ports	4x 25G SFP28 (kartela APM414V e përfshirë)
Console	1x RJ45 RS-232, 1x USB-C, 2x USB-A
Modular interface slot	1 (opsionale: APM414C, APM414SD, APM414LD)
Network	
Switching capacity	280 Gb/s
Forwarding rate	208.32 Mpps
Packet buffer	32 MB
MAC address table	16K
Jumbo frame support	deri 12 KB
VLAN support	4000
Layer	L3 (static, policy-based dhe dynamic routing)
Stacking	Virtual Chassis (NSF, hitless failover)
AV protocols	Dante, NDI, Q-SYS, AES67, IPMX, SDVoE, AVB, ST 2110
Power over Ethernet (PoE)	
PoE standard	802.3bt Type 4 (PoE++)
PoE ports	16
PoE budget (base)	530 W (1+1 redundancy)
PoE budget (max)	1,130 W
Per-port PoE power	deri 100 W

Power supply	
Internal PSUs	2x 800W
Power connector	2x Neutrik powerCON
Max power consumption (with PoE)	1,359.8 W
Processor	
CPU	ARM Cortex A57 Quad-Core, deri 1.8 GHz
Memory	
RAM	4 GB DDR4 GB
Storage	
Flash memory	512 MB
Management features	
Management software	NETGEAR AV OS, Engage Controller, web GUI, CLI
IGMP	NETGEAR IGMP Plus (enhanced)
PTP profiles	SMPTE ST 2059-2, AES67, AES-R16-2016
AVB support	Po
Weight & dimensions	
Width	440 mm
Depth	432 mm
Height	43.2 mm (1U)
Weight	7.85 kg
Technical details	
MTBF	355,650 ore