PLANET

Switch Industrial PLANET IGS-6325-16P4S, 16 porta Gigabit PoE+, 4 porta SFP 1G/2.5G, PoE 360W, Managed Layer 3, Switching Capacity 52Gbps, IP30, DIN-Rail - Hiri/Blu

SKU: 26030989 · EAN: 4711605284134

SPECIFIKAT TEKNIKE

70 specifikat e produktit

ATRIBUTI	VLERA
Management features	
Switch type	Managed
Switch layer	L3
Feature	Quality of Service (QoS) support
Feature	Web-based management
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	16
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP+ modules quantity	4
Console port	RJ-45
Power connector	Terminal block (3-pin)
Network	
Copper ethernet cabling technology	10BASE-T, 100BASE-FX, 100BASE-TX, 1000BASE-LX, 1000BASE-SX, 1000BASE-T
Feature	Port mirroring
Feature	Full duplex
Feature	IP routing
Routing entries	128
Feature	Flow control support
Feature	Link aggregation
Feature	Broadcast storm control
Feature	Auto MDI/MDI-X
Feature	Spanning tree protocol
Feature	Auto-negotiation
Feature	VLAN support
Virtual LAN features	MAC address-based VLAN, Multicast VLAN, Private VLAN, Protocol-based VLAN, Tagged VLAN, Voice VLAN

Number of VLANs	4094
Data transmission	
Switching capacity	52 Gbit/s
Throughput	38.6 Mpps
MAC address table	16000 entries
Feature	Store-and-forward
Number of trunks	10
Feature	Static route
Number of static routes	128
Feature	Jumbo frames support
Jumbo frames	10000
Packet buffer memory	32 MB
Security	
Feature	Access Control List (ACL)
Feature	IGMP snooping
IGMP entries	255
Security algorithms	SNMP, SNMPv3, SSH, SSL/TLS
Feature	Loop protection
Feature	BPDU filtering/protection
Authentication	Port-based authentication
Queue scheduling algorithms	Priority queuing (PQ), Weighted Round Robin (WRR)
Multicast features	
Feature	Multicast support
Multicast Listener Discovery (MLD) snooping	v1/v2
MLD entries	255
Protocols	
Feature	GARP VLAN Registration Protocol (GVRP)
Routing protocols	OSPF
IPv4 & IPv6 features	IPv6 Telnet
Design	
Product colour	Aluminium, Blue
Housing material	Aluminium
Feature	Reset button
LED indicators	Activity, Fault, Link, PoE, Power, Ring
International Protection (IP) code	IP30

Feature	Wall mountable
Feature	DIN rail mounting
Power	
DC input voltage	48 - 56 V
Power consumption (max)	344 W
Power over Ethernet (PoE)	
Feature	Power over Ethernet (PoE)
Power over Ethernet (PoE) ports quantity	16
Power over Ethernet (PoE) power per port	36 W
Total Power over Ethernet (PoE) budget	320 W
Operational conditions	
Operating temperature (T-T)	-40 - 75 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	5 - 95%
Heat dissipation	1173.04 BTU/h
Weight & dimensions	
Width	76 mm
Depth	135 mm
Height	152 mm
Weight	1.53 kg
Certificates	
Certification	FCC Part 15 Class A, CEIEC60068-2-32 (free fall)IEC60068-2-27 (shock)IEC60068-2-6 (vibration)
Logistics data	
Harmonized System (HS) code	85176990