PLANET

Switch Industrial PLANET IGS-4215-8P2T2S, 8 porta Gigabit PoE+, 2 porta Gigabit RJ45, 2 porta SFP 1G, PoE 240W, Managed Layer 2/4, Switching Capacity 24Gbps, IP30, DIN-Rai - Blu/Hiri

SKU: 26030969 · EAN: 4711605282819

SPECIFIKAT TEKNIKE

61 specifikat e produktit

ATRIBUTI	VLERA
Management features	
Switch type	Managed
Switch layer	L2/L4
Feature	Quality of Service (QoS) support
Feature	Web-based management
Feature	ARP inspection
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	10
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
SFP+ module slots quantity	2
Fiber optic connector	SFP
Console port	RJ-45
Network	
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Feature	Port mirroring
Feature	Full duplex
Feature	Half duplex
Feature	Link aggregation
Feature	Auto MDI/MDI-X
Feature	Spanning tree protocol
Feature	VLAN support
Virtual LAN features	Private VLAN, Tagged VLAN, Protocol-based VLAN
Number of VLANs	4094
Optical fiber	
Fiber ethernet cabling technology	1000BASE BX, 1000BASE LX, 1000BASE SX

Data transmission	
Switching capacity	24 Gbit/s
Throughput	17.85 Mpps
MAC address table	8000 entries
Feature	Store-and-forward
Number of queues	8
Feature	Jumbo frames support
Jumbo frames	10000
Packet buffer memory	4.1 MB
Security	
DHCP features	DHCP snooping
Feature	Access Control List (ACL)
Security algorithms	SNMP, SNMPv3, SSH, SSL/TLS
Feature	Loop protection
Authentication type	IEEE 802.1x, RADIUS
Multicast features	
Feature	Multicast support
Design	
Product colour	Blue, Silver
Housing material	Aluminium
Feature	Reset button
LED indicators	Activity, Link, PoE, Power, System
International Protection (IP) code	IP30
Feature	Wall mountable
Feature	DIN rail mounting
Power	
DC input voltage	48 - 56 V
Power consumption (max)	242 W
Feature	Surge protection
Surge protection voltage	6 kV
Power over Ethernet (PoE)	
Feature	Power over Ethernet (PoE)
Power over Ethernet plus (PoE+) ports quantity	8
Power over Ethernet (PoE) power per port	36 W
Total Power over Ethernet (PoE) budget	240 W

Other features	
Feature	Terminal block port
Operational conditions	
Operating temperature (T-T)	-40 - 75 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%
Weight & dimensions	
Width	76.8 mm
Depth	107.3 mm
Height	152 mm
Weight	1.04 kg
Certificates	
Certification	FCC Part 15 Class A, CEIEC 60068-2-32 (free fall)IEC 60068-2-27 (shock)IEC 60068-2-6 (vibration)
Logistics data	
Harmonized System (HS) code	85176990