CyberPower

CyberPower BP48VP2U03 Batterieerweiterungsmodul Tower/Rack 2U, PP75 Anschluss (1), 48Vdc, 6Ah/12V *16, integriertes Ladegerät, komp. mit PR2200ERTXL2UA(N)/PR3000ERTXL2UA(N) inkl. 19" Railkit



Marke : CyberPower

Artikel-Code: BP48VP2U03

Produktname : BP48VP2U03 Batterieerweiterungsmodul Tower/Rack 2U, PP75 Anschluss (1), 48Vdc, 6Ah/12V *16, integriertes Ladegerät, komp. mit PR2200ERTXL2UA(N)/PR3000ERTXL2UA(N) inkl. 19" Railkit

BP48VP2U03 Batterieerweiterungsmodul Tower/Rack 2U, PP75 Anschluss (1), 48Vdc, 6Ah/12V *16, integriertes Ladegerät, komp. mit PR2200ERTXL2UA(N)/PR3000ERTXL2UA(N) inkl. 19" Railkit

CyberPower BP48VP2U03 Batterieerweiterungsmodul Tower/Rack 2U, PP75 Anschluss (1), 48Vdc, 6Ah/12V *16, integriertes Ladegerät, komp. mit PR2200ERTXL2UA(N)/PR3000ERTXL2UA(N) inkl. 19" Railkit:

CyberPower BP48VP2U03 ist eine externe Batterieerweiterung (EBM), die in Verbindung mit kompatiblen USV-Systemen verwendet werden kann, um eine längere Systemlaufzeit bei Stromunterbrechung zu gewährleisten. Das Batteriemodul verfügt über DC-Plug-and-Play-Stromanschlüsse zum Hinzufügen mehrerer EBMs.

Das Produkt verfügt über Hot-Swap-fähige Akkupacks, mit denen Benutzer das Batteriemodul sicher austauschen können, ohne die angeschlossenen Verbraucher zu unterbrechen. Die im EBM verwendete versiegelte Bleibatterie ist wartungsfrei und sicher, was die zuverlässige Leistung des Stromsystems gewährleistet. Das Produkt ist mit einem Metallgehäuse in Industriequalität ausgestattet und eignet sich für Rechenzentren und kritische Anwendungen.

Merkmale	
Akku-/Batteriespannung *	12 V
Batteriekapazität *	6 Ah
Anzahl enthaltener Akkus/Batterien *	16 Stück(e)
Produktfarbe	Schwarz
Hot-Swap-Batterie	✔
Akkuladezeit	6 h
Kompatibilität	PR2200ERTXL2UAN PR3000ERTXL2UAN
Zertifikate	
Konformitätsbescheinigungen	RoHS
Akku/Batterie	
Akku-/Batterietechnologie *	Plombierte Bleisäure (VRLA)
Nachhaltigkeit	
Nachhaltigkeitskonformität	✔
Gewicht und Abmessungen	
Gewicht	41,1 kg

Gewicht und Abmessungen	
Breite	433 mm
Höhe	86,5 mm
Tiefe	630 mm
Verpackungsdaten	
Verpackungsbreite	575 mm
Verpackungshöhe	275 mm
Verpackungstiefe	765 mm
Paketgewicht	48,2 kg
Verpackungsgewicht	48,2 kg
Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Logistikdaten	
Warentarifnummer (HS)	8504909000
Ursprungsland	China



0649532930753

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 01-JUL-2026. Prints or copies of Information are only valid on the printed Publication date