GRANDSTREAM

VoIP Grandstream SIP GRP-2616 Profesional Biznes

SKU: 12002279 · EAN: 6947273702955

SPECIFIKAT TEKNIKE

52 specifikat e produktit

ATRIBUTI	VLERA
Design	
Product type	IP Phone
Handset type	Wired handset
Product colour	Black
Performance	
Dual-Tone Multi-Frequency (DTMF) modes	In-band, Out-of band, SIP info
Password protection type	Supervisor, User
Phone features	
Lines quantity	6 lines
Answering machine	Yes
Call log entries	2000
Call waiting	Yes
Call hold	Yes
Call forwarding	Yes
Conference call	Yes
Call park	Yes
Call pick up	Yes
Phonebook sharing	Yes
Call transfer	Yes
Management features	
Number of programmable keys	5
Firmware upgradeable	Yes
Display	
Display	TFT
Display diagonal	10.9 cm (4.3")
Display resolution	480 x 272 pixels
Touchscreen	No

Camera	
Front camera	No
Audio	
Speakerphone	Yes
Voice codecs	G.711a, G.711u, G.722, G.723, G.726, G.729ab, OPUS, iLBC
Network	
Ethernet LAN	Yes
Ethernet LAN interface type	Gigabit Ethernet
Wi-Fi	Yes
Bluetooth	Yes
Supported network protocols	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS(A record, SRV, NAPTR), DHCP, PPPoE, TELNET, TFTP, NTP, STUN, SIMPLE, LLDP, LDAP, TR-069, 802.1x, TLS, SRTP, IPV6
Quality of Service (QoS) support	Yes
Security algorithms	256-bit AES, MD5, SRTP, SSL/TLS
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3af
Ports & interfaces	
USB 2.0 ports quantity	1
Ethernet LAN (RJ-45) ports	2
RJ-9 ports quantity	1
Certificates	
Certification	FCC: 15 B; 15 C 15.247; 15 E 15.407; FCC Part68 HAC; 1 I(MPE)CE: EN 55032; EN 55035; EN 61000-3-2; EN 61000-3-3; EN 62368-1; EN 301489-1; EN301489-17; EN 300328; EN 301893; EN 62311RCM: AS/NZS CISPR32; AS/NZS 4268; AS/NZS 62368.1; AS/CA S004; AS NZS 2772.2IC: ICES-003; CS-03; RSS-247; RSS-102(MPE).
Power	
Power over Ethernet (PoE)	Yes
AC adapter input voltage	100 - 240 V
AC adapter output voltage	12 V
AC adapter output current	1 A
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%
Storage temperature (T-T)	-10 - 60 °C
Weight & dimensions	
Width	247 mm

Depth	228 mm
Height	82.4 mm
Weight	1.02 kg
Package weight	1.65 kg
Packaging content	
Number of handles included	1 pc(s)
Logistics data	
Harmonized System (HS) code	85171800