SYNOLOGY

NAS Synology RackStation RS3626xs, Intel Xeon D-1726, 8GB DDR4 ECC, 12 Bay, 2 × 10GbE, 2U Rackmount - Zezë

SKU: 26031733 · EAN: 4711174726073

SPECIFIKAT TEKNIKE

79 specifikat e produktit

ATRIBUTI	VLERA
Storage	
Storage drive capacity	0 GB
Storage drive interface	Serial ATA, Serial ATA II, Serial ATA III
Storage drive sizes supported	2.5,3.5"
Feature	RAID support
RAID levels	F1, JBOD, 0, 1, 5, 10
Feature	Hot-swap drive bays
Supported file systems	BTRFS, ext4, ext3, FAT32, NTFS, HFS+, exFAT
Total installed storage capacity	0 TB
Number of storage drives supported	12
Installed storage drive type	No
Supported storage drive types	HDD & SSD
Maximum number of drives (with expansion)	36
Processor	
Processor manufacturer	Intel
Processor family	Intel® Xeon® D
Processor model	D-1726
Processor frequency	2.9 GHz
Processor boost frequency	3.5 GHz
Processor cores	6
Processor threads	12
Processor cache	10 MB
Number of processors installed	1
Thermal Design Power (TDP)	70 W
Memory	
Internal memory	8 GB
Internal memory type	DDR4

Maximum RAM supported	48 GB
Memory slots	6
Memory form factor	UDIMM
Feature	ECC
Network	
Feature	Ethernet LAN
Ethernet LAN data rates	10,100,1000,10000 Mbit/s
Ethernet LAN data rate supported (max)	10000 Mbit/s
Feature	Wake-on-LAN ready
Feature	Wake-on-WAN ready
Ports & interfaces	
Feature	USB port
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
Ethernet LAN (RJ-45) ports	2
Expansion ports quantity	2
PCI Express x8 (Gen 4.x) slots	2
Design	
Chassis type	Rack (2U)
Cooling type	Active
Product colour	Black
Number of fans	4 fan(s)
Fan diameter	8 cm
Fan diameter 2	8 cm
LED indicators	Power, Status, Alarm
Performance	
Type	NAS
Device class	Small & Medium Business
Feature	Backup function
Number of users	3300 user(s)
Noise level	38.8 dB
Feature	Snapshot
Feature	Access Control List (ACL)
Feature	Reset button
Feature	On/off switch
Browser supported	Chrome Firefox Edge Safari

Software	
Operating system installed	DiskStation Manager
Power	
Power supply unit (PSU) capacity	550 W
Feature	Redundant power supply (RPS) support
Power consumption (typical)	147.79 W
Power consumption (HDD standby)	75.73 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Number of phases	1
Weight & dimensions	
Width	482 mm
Depth	724 mm
Height	88 mm
Weight	14.5 kg
Packaging content	
Cables included	AC
Operational conditions	
Operating temperature (T-T)	0 - 35 °C
Operating relative humidity (H-H)	8 - 80%
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	5 - 95%
Operating altitude	0 - 5000 m
Other features	
Size (imperial)	48.3 cm (19")
Supported protocols	SMBAFPNFSFTPWebDAVRsync
Expansion type	Mini-SAS HD
Doesn't contain	Lead, Mercury, Cadmium
Warranty period	5 year(s)
Compliance certificates	Federal Communications Commission (FCC), CE, BSMI, VCCI, UKCA, EAC, CCC, KC, BIS, UL, RoHS