

SYNOLOGY

NAS Synology RackStation RS1226RP+, AMD Ryzen V1500B, 4GB DDR4 ECC, 8 Bay, 2 × 2.5GbE, 2U Rackmount, PSU redundant - Zezë

SKU: 26031740 · EAN: 4711174726875

SPECIFIKAT TEKNIKE	
76 specifikat e produktit	
ATRIBUTI	VLERA
Storage	
Storage drive capacity	0 GB
Supported storage drive interfaces	M.2, Serial ATA III
Storage drive sizes supported	2.5,3.5,M.2
Feature	NVMe
Feature	RAID support
RAID levels	JBOD, 0, 1, 5, 6, 10
Feature	Hot-swap drive bays
Supported file systems	BTRFS, ext4, ext3, FAT32, NTFS, HFS+, exFAT
Total installed storage capacity	0 TB
Number of storage drives supported	8
Installed storage drive type	No
Supported storage drive types	HDD & SSD
Maximum number of drives (with expansion)	12
Processor	
Processor manufacturer	AMD
Processor family	AMD Ryzen
Processor model	V1500B
Processor frequency	2.2 GHz
Processor cores	4
Processor threads	8
L2 cache	2 MB
Number of processors installed	1
Processor operating modes	64-bit
Thermal Design Power (TDP)	16 W

Memory	
Internal memory	4 GB
Internal memory type	DDR4
Maximum RAM supported	32 GB
Memory slots	2
Memory form factor	SO-DIMM
Feature	ECC
Network	
Feature	Ethernet LAN
Ethernet LAN data rates	2500 Mbit/s
Feature	Wake-on-LAN ready
Feature	Wake-on-WAN ready
Ports & interfaces	
Feature	USB port
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
Ethernet LAN (RJ-45) ports	2
Expansion ports quantity	1
PCI Express x8 (Gen 3.x) slots	1
Design	
Chassis type	Rack (2U)
Cooling type	Active
Product colour	Black
Number of fans	2 fan(s)
Fan diameter	8 cm
Fan diameter 2	8 cm
LED indicators	Power, Status, Alarm
Performance	
Type	NAS
Device class	Small & Medium Business
Feature	Backup function
Noise level	22.8 dB
Feature	Snapshot
Feature	Reset button
Feature	On/off switch
Browser supported	Chrome Firefox Edge Safari

Software	
Operating system installed	Synology DSM
Power	
Power supply unit (PSU) capacity	550 W
Feature	Redundant power supply (RPS) support
Power consumption (typical)	81.82 W
Power consumption (HDD standby)	30.58 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Number of phases	1
Weight & dimensions	
Width	481.9 mm
Depth	398.4 mm
Height	88.3 mm
Weight	8.9 kg
Packaging content	
Cables included	Power
Power cables quantity	2
Operational conditions	
Operating temperature (T-T)	0 - 35 °C
Operating relative humidity (H-H)	8 - 80%
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	5 - 95%
Operating altitude	0 - 5000 m
Other features	
Size (imperial)	48.3 cm (19")
Expansion type	USB Type-C
Doesn't contain	Lead, Mercury, Cadmium
Compliance certificates	Federal Communications Commission (FCC), CE, BSMI, VCCI, RCM, UKCA, EAC, CCC, KC, BIS, UL, RoHS