LANCOM

Switch LANCOM XS-3526YUP, 16x Gigabit Ethernet PoE+, 8x 10Gbps PoE++, 2x SFP28 25Gbps, PoE 720W, Layer 3 Lite, Rackmount 1U - Zezë

SKU: 26030218 · EAN: 4044144618901

SPECIFIKAT TEKNIKE

71 specifikat e produktit

ATRIBUTI	VLERA
Network	
Feature	Port mirroring
Networking standards	IEEE 802.1D, IEEE 802.1s, IEEE 802.1w, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
Feature	10G support
Cable types supported	Cat6, Cat7
Feature	IP routing
Feature	Flow control support
Feature	Link aggregation
Feature	Broadcast storm control
Feature	Rate limiting
Feature	VLAN support
Virtual LAN features	Voice VLAN
Number of VLANs	4093
Management features	
Switch type	Managed
Switch layer	L2/L3
Feature	Quality of Service (QoS) support
Feature	Configuring Location Settings (CLI)
Feature	System event log
MIB support	MIB II, Bridge MIB, Interface MIB, SMON MIB, IGMP MIB
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	2.5G Ethernet (100/1000/2500)
Gigabit Ethernet (copper) ports quantity	16
10G Ethernet (copper) ports quantity	8

Console port	RJ-45
SFP28 ports quantity	2
Power connector	AC-in jack
Data transmission	
Throughput	292 Gbit/s
MAC address table	32000 entries
Feature	Static route
Feature	Jumbo frames support
Jumbo frames	10240
Packet buffer memory	4 MB
Security	
DHCP features	DHCP server
Feature	Access Control List (ACL)
Feature	IGMP snooping
IGMP entries	1024
Feature	IGMP proxy
Feature	MAC address filtering
Feature	Static port security
Feature	SSH/SSL support
Authentication type	IEEE 802.1x, RADIUS, TACACS+
Multicast features	
Feature	Multicast support
Multicast Listener Discovery (MLD) snooping	Y
Protocols	
Feature	GARP VLAN Registration Protocol (GVRP)
Design	
Feature	Rack mounting
Form factor	1U
Product colour	Black
Housing material	Metal
LED indicators	Yes
Number of fans	1 fan(s)
Performance	
Noise level	48 dB
Power	

Power source	AC
Feature	Power supply included
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	865 W
Power over Ethernet (PoE)	
Feature	Power over Ethernet (PoE)
Power over Ethernet (PoE) ports quantity	8
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 90%
Heat dissipation	375 BTU/h
Weight & dimensions	
Width	442 mm
Depth	375 mm
Height	44 mm
Weight	4.9 kg
Packaging content	
Feature	Manual
Packaging data	
Package width	480 mm
Package depth	570 mm
Package height	100 mm
Package weight	5.22 kg
Logistics data	
Customs product code (TARIC)	85176200
Country of origin	Taiwan