KEBA ENERGY AUTOMATION GMBH

Stacion Karikimi KEBA P30 x-series, 22 kW, Kabllo Type 2 6 m, RFID – Zezë

SKU: 99056454 · EAN: 9120050716377

SPECIFIKAT TEKNIKE

33 specifikat e produktit

ATRIBUTI	VLERA
Design	
Model	KEBA KeContact P30 x-series KC-P30-EC2404B2-M0A-GE
Housing material	Plastic
Mounting	Wall mounting (indoor/outdoor)
Colour	Green Edition
Performance	
Max charging power	22 kW
Charging mode	Mode 3 (IEC 61851-1)
Phases	1-phase / 3-phase
Rated supply voltage	3 x 230 V / 400 V (50 Hz)
Rated current (configurable)	10 A / 13 A / 16 A / 20 A / 25 A / 32 A
Charging points	1
Ports & interfaces	
Connector type	Type 2 (IEC 62196-2)
Cable length	6 m (fixed)
USB interface	USB-A 2.0, max. 500 mA
Ethernet	10/100 Mbit/s (RJ45)
Network	
Connectivity	Wi-Fi (WLAN)
Protocol	OCPP 1.5 / 1.6, Modbus TCP, UDP
Features	
RFID	Yes (MIFARE, ISO 14443 / ISO 15693)
ISO 15118 (Plug & Charge)	Hardware-ready
Energy meter	MID-certified
DC fault current detection	Yes
Load management	Hub (master for up to 15 P30 c-series units)
PV surplus charging	Yes

Display	Yes (LED strip + display)
LTE	No
Circuit breaker integrated	No
Technical details	
IP rating	IP54
Impact resistance	IK10
Operating temperature	-30 °C to +50 °C
Weight & dimensions	
Height	643 mm
Width	240 mm
Depth	142 mm
Weight	7.8 kg
Certificates	
CO2 footprint	CO2-neutral (Green Edition)