

CYBERPOWER

UPS CyberPower OLS3000ERT2UA, 3000 VA, 2700 W, Online, 8 Priza IEC C13, 2 Priza IEC C19, Rack/Tower 2U – Zezë

SKU: 99056246 · EAN: 4712856273823

SPECIFIKAT TEKNIKE

84 specifikat e produktit

ATRIBUTI	VLERA
Battery	
Battery capacity	9 Ah
Battery technology	Sealed Lead Acid (VRLA)
Battery voltage	48 V
Number of batteries supported	3
Number of batteries included	2 pc(s)
Typical backup time at full load	3.8 min
Typical backup time at half load	13.1 min
Battery life (max)	5 year(s)
Battery recharge time	4 h
Charging current	1.5 A
Feature	Hot-swap battery
Replacement battery cartridge	RBP0157
Features	
UPS topology	Double-conversion (Online)
Output power capacity	2 kVA
Output power	1800 W
Waveform	Pure sine
Input operation voltage (min)	190 V
Input operation voltage (max)	300 V
Input frequency	50/60 Hz
Output operation voltage (min)	208 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Output frequency regulation	0.5 Hz
Output voltage regulation	1%

Maximum current	9 A
Surge energy rating	363 J
Response time	0 ms
Heat dissipation	682 BTU/h
Efficiency (ECO mode)	95%
Power factor	0.9
Input power factor	0.99
Output power factor	0.9
Crest factor	3:1
Feature	ECO mode
Feature	Emergency Power Off (EPO)
Output voltage Total Harmonic Distortion (THD)	5%
Feature	EMI/RFI noise filtering
Feature	Surge protection
Power protection features	Overload
Feature	Audible alarm(s)
Audible alarm modes	Battery replacement, Low battery alarm, Overload alarm, Fault, Alarm when on battery
Ports & interfaces	
AC outlet types	C13 coupler
Power plug	Type F
AC outlets quantity	8 AC outlet(s)
Feature	USB port
USB port type	USB Type-B
Feature	Serial interface
Serial interface type	RS-232
Serial ports quantity	1
RS-232 ports	1
Modem (RJ-11) ports	1
Ethernet LAN (RJ-45) ports	1
Feature	Emergency Power Off (EPO) connector
Design	
Form factor	Rackmount/Tower
Housing material	Metal
Rack capacity	2U
Cable length	1.5 m

Cooling type	Active
Feature	Built-in fan
Product colour	Black
Control type	Buttons
Display type	LCD
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	-20 - 50%
Operating altitude	0 - 1500 m
Non-operating altitude	0 - 1500 m
Certificates	
Compliance certificates	CE, EAC, RoHS
Certification	CE, EAC
Packaging content	
Feature	Batteries included
Feature	Rack mount kit
Cables included	Input power cable, USB cable
Feature	Manual
Weight & dimensions	
Width	438 mm
Depth	610 mm
Height	88 mm
Weight	19.2 kg
Packaging data	
Package width	540 mm
Package depth	550 mm
Package height	230 mm
Package weight	23.4 kg
Logistics data	
Harmonized System (HS) code	8504408590
Country of origin	China