

ROLINE

UPS ROLINE LineSecure III 1500, 1500 VA, 1200 W, Line-Interactive, 8 Priza IEC C13, Tower – Zezë

SKU: 99056381 · EAN: 7630049627970

SPECIFIKAT TEKNIKE

55 specifikat e produktit

ATRIBUTI	VLERA
Features	
UPS topology	Line-Interactive
Output power capacity	1.5 kVA
Output power	1200 W
Waveform	Pure sine
Input operation voltage (min)	100 V
Input operation voltage (max)	240 V
Input frequency	50/60 Hz
Output operation voltage (min)	100 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Feature	Automatic Voltage Regulation (AVR)
Response time	4 ms
Efficiency	95%
Noise level	40 dB
Feature	Surge protection
Surge protection features	Fax, Telephone
Power protection features	Overload, Short circuit
Feature	Maintenance-free
Ports & interfaces	
AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	8 AC outlet(s)
Feature	USB port
USB 2.0 ports quantity	1
USB port type	USB Type-B
Feature	Serial interface

Serial interface type	RS-232
RS-232 ports	1
Modem (RJ-11) ports	1
Feature	Network card slot
Ethernet LAN (RJ-45) ports	1
Battery	
Battery technology	Lead-Acid
Battery capacity	7.2 Ah
Battery voltage	12 V
Number of batteries supported	2
Number of batteries included	2 pc(s)
Typical backup time at full load	3 min
Typical backup time at half load	6 min
Battery recharge time(90%)	4 h
Design	
Form factor	Tower
Cooling type	Active
Feature	Built-in fan
Product colour	Black
Control type	Buttons
Display type	LCD
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 90%
Packaging content	
Feature	Batteries included
Weight & dimensions	
Width	140 mm
Depth	380 mm
Height	210 mm
Weight	15 kg
Packaging data	
Package width	260 mm
Package depth	500 mm
Package height	330 mm

Package weight

16.8 kg
