

GIGASET

Telefon VoIP Gigaset N530 IP PRO + S700H PRO, DECT, 8 llogari SIP, deri në 8 thirrje njëkohësisht, Bluetooth - Bardhë/Zezë

SKU: 26029423 · EAN: 4255781907697

SPECIFIKAT TEKNIKE	
59 specifikat e produktit	
ATRIBUTI	VLERA
Performance	
Type	DECT telephone
Handset type	Wireless handset
Number of melodies	32
Feature	GAP compatible
Feature	On/off key
Design	
Mounting type	Desk
Product colour	Anthracite
Feature	Backlight buttons
Feature	Keypad lock
Protection features	Scratch resistant
Phone features	
Feature	Speakerphone
Phonebook capacity	500 entries
Feature	Short Message Service (SMS)
Feature	VIP group function
Feature	VIP group with own melody
Feature	Vibrating alert
Call management	
Feature	Caller ID
Feature	Redialing
Call log entries	60
Feature	Calling line identification presentation (CLIP)
Management features	
Feature	Navigation key

Volume control	Buttons
Personalization	Icons, Ringtones
Feature	Clock with calendar
Feature	Calendar
Feature	Programmable hot keys
Languages support	Multi
Indication	
Feature	Battery capacity indicator
Feature	Battery charge indicator
Feature	Battery full indication
Feature	Battery low indication
Display	
Display	TFT
Display diagonal	6.1 cm (2.4")
Display size (HxV)	49 x 37 mm
Display resolution	240 x 320 pixels
Feature	Backlight display
Feature	Built-in display
Ports & interfaces	
Feature	Power over Ethernet (PoE)
Feature	Wireless connection
Headset connectivity	Bluetooth
Power	
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Output power	5 W
Battery type	AAA
Number of batteries supported	2
Battery technology	Nickel-Metal Hydride (NiMH)
Talk time	13 h
Standby time	320 h
Multimedia	
Audio formats supported	G.711 A-law, G.711 µ-law, G.722
Weight & dimensions	
Base dimensions (WxDxH)	40 x 81 x 80 mm

Handset dimensions (WxDxH)	49 x 26 x 151 mm
Packaging data	
Package type	Box
Packaging content	
Number of handsets included	1
Feature	Base station
Feature	Manual
Sustainability	
Compliance certificates	CE
Operational conditions	
Operating temperature (T-T)	5 - 45 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	20 - 75%