CISCO

Switch Cisco Business CBS220-24T-4G, 24x Gigabit Ethernet RJ45, 4x Gigabit SFP, Smart Managed, Switching Capacity 56Gbps, Rackmount 1U - Hiri

SKU: 26030283 · EAN: 0889728344807

SPECIFIKAT TEKNIKE

61 specifikat e produktit

ATRIBUTI	VLERA
Management features	
Switch type	Managed
Switch layer	L2
Feature	Quality of Service (QoS) support
Feature	Web-based management
Feature	System event log
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
SFP+ module slots quantity	4
Network	
Feature	10G support
Feature	Port mirroring
Feature	IP routing
Feature	Flow control support
Feature	Link aggregation
Feature	Broadcast storm control
Feature	Auto MDI/MDI-X
Feature	Spanning tree protocol
Feature	Head-of-line (HOL) blocking
Ethernet LAN data rates	10,100,1000 Mbit/s
Feature	VLAN support
Number of VLANs	256
Data transmission	
Switching capacity	56 Gbit/s
Forwarding rate	41.66 Mpps

MAC address table	8192 entries
Number of queues	8
Feature	Jumbo frames support
Jumbo frames	9216
Packet buffer memory	4.1 MB
Security	
DHCP features	DHCP client
Feature	Access Control List (ACL)
Feature	IGMP snooping
Security algorithms	SNMP, SNMPv2, SNMPv3
Feature	MAC address filtering
Feature	SSH/SSL support
Feature	Loop protection
Feature	BPDU filtering/protection
Authentication type	IEEE 802.1x, RADIUS
Queue scheduling algorithms	Weighted Round Robin (WRR)
Multicast features	
Feature	Multicast support
Multicast MAC address table	8192 entries
Protocols	
Management protocols	SNMP v1/2c/3, Telnet, TFTP, HTTP/HTTPS, SNTP
Design	
Feature	Rack mounting
Form factor	1U
Product colour	White
Feature	Reset button
LED indicators	Yes
Performance	
Feature	Built-in processor
Internal memory	256 MB
Flash memory	64 MB
Feature	Firmware upgradeable
Power	
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz

Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%
Heat dissipation	61.42 BTU/h
Weight & dimensions	
Width	440 mm
Depth	203 mm
Height	44 mm
Weight	2.75 kg
Logistics data	
Harmonized System (HS) code	85176990