CyberPower

CyberPower CP1000EIPFCRM1U uninterruptible power supply (UPS) Line-Interactive 1000 kVA 600 W 6 AC outlet(s)



Brand : CyberPower

Product code: CP1000EIPFCRM1U

Product name : CP1000EIPFCRM1U



CyberPower CP1000EIPFCRM1U. UPS topology: Line-Interactive, Output power capacity: 1000 kVA, Output power: 600 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 6 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 2.2 min, Typical backup time at half load: 10.5 min. Form factor: Rackmount, Product colour: Black, Silver, Housing material: Metal. Compliance certificates: CE, RoHS

Features	
UPS topology *	Line-Interactive
Output power capacity *	1000 kVA
Output power *	600 W
Waveform *	Pure sine
Input operation voltage (min) *	165 V
Input operation voltage (max) *	271 V
Input frequency *	50/60 Hz
Output frequency	50/60 Hz
Output frequency regulation	3 Hz
Automatic Voltage Regulation (AVR)	✔
Maximum current	10 A
Surge energy rating	450 J
Response time	7 ms
Heat dissipation	18.4 BTU/h
Number of input phases	1
Number of output phases	1
Power factor	0.6
Power Factor Correction (PFC) type	Active
Surge protection	✔
Audible alarm(s)	✔
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Power source type	AC
Socket circuit breaker	✔

Ports & interfaces	
AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	6 AC outlet(s)
Serial interface	✔
Serial ports quantity	1
Ethernet LAN (RJ-45) ports	2

Battery	
Battery technology	Sealed Lead Acid (VRLA)
Typical backup time at full load	2.2 min
Typical backup time at half load	10.5 min

Battery	
Battery recharge time	8 h
Hot-swap battery	✔
Rechargeable battery	✔

Design	
Form factor *	Rackmount
Housing material	Metal
Cable length	1.83 m
Product colour *	Black, Silver
Display type	LCD
LED indicators	✔

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Certificates	
Compliance certificates	CE, RoHS

Packaging content	
Quick installation guide	✔

Sustainability	
Sustainability compliance	✔

Weight & dimensions	
Width	433 mm
Depth	388.7 mm
Height	44 mm
Weight	13.4 kg

Packaging data	
Package width	530 mm
Package depth	494 mm
Package height	158 mm
Package weight	15.5 kg

Other features	
Battery type	RBP0025
Nominal output voltage	230 V
Nominal input voltage	220-240 V
Overload protection	✔

4711027798028

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 31-OCT-2026. Prints or copies of Information are only valid on the printed Publication date