EIZO

EIZO 61.0cm (24") CS2400S 16:10 HDMI+DP+USB-C IPS black

SKU: 16008693 · EAN: 4995047066194

SPECIFIKAT TEKNIKE

99 specifikat e produktit

ATRIBUTI	VLERA
Display	
Display diagonal	61.2 cm (24.1")
Display resolution	1920 x 1200 pixels
HD type	WUXGA
Native aspect ratio	16:10
Display technology	LCD
Panel type	IPS
LED backlight	Yes
Backlight type	W-LED
Touchscreen	No
Display brightness (typical)	410 cd/m²
Response time	19 ms
Anti-glare screen	Yes
Screen shape	Flat
Supported graphics resolutions	1920 x 1200 (WUXGA), 1920 x 1080 (HD 1080)
Supported video modes	1080p, 1080i, 720p, 576p, 576i, 480p, 480i
Contrast ratio (typical)	1350:1
Maximum refresh rate	60 Hz
Viewing angle. horizontal	178°
Viewing angle. vertical	178°
Display number of colours	1.07 billion colours
Pixel pitch	0.27 x 0.27 mm
Pixel density	94 ppi
Horizontal scan range	15 - 76 kHz
Vertical scan range	23 - 61 Hz
Viewable size. horizontal	51.8 cm
Viewable size. vertical	32.4 cm

Display diagonal (metric)	61.1 cm
Colour depth	10 bit
Colour gamut standard	Adobe RGB, DCI-P3, sRGB
sRGB coverage (typical)	100%
Adobe RGB coverage	99%
DCI-P3 coverage	99%
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Flicker-free technology	Yes
Multimedia	
Built-in speaker(s)	No
Built-in camera	No
Design	
Market positioning	Photo editing
Product colour	Black
Feet colour	Black
Ports & interfaces	
Built-in USB hub	Yes
USB hub version	2.0 / 3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-B, USB Type-C
Number of upstream ports	2
Number of USB Type-B upstream ports quantity	1
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	4
USB Type-C DisplayPort Alternate Mode	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	70 W
HDMI	Yes
HDMI ports quantity	1
DisplayPorts quantity	1
Built-in KVM switch	Yes
HDCP	Yes
HDCP version	2.3
Ergonomics	

VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Height adjustment	Yes
Adjustable height (max)	15.5 cm
Pivot	Yes
Pivot angle	0 - 90°
Swivelling	Yes
Swivel angle range	0 - 344°
Tilt adjustment	Yes
Tilt angle range	-5 - 35°
On Screen Display (OSD)	Yes
Power	
Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	16 kWh
Power consumption (typical)	18 W
Power consumption (standby)	0.3 W
Power consumption (max)	149 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	0 - 35 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width (with stand)	554.4 mm
Depth (with stand)	245 mm
Height (with stand)	396 mm
Weight (with stand)	8.2 kg
Width (without stand)	554.4 mm
Depth (without stand)	64 mm
Height (without stand)	362 mm

Weight (without stand)	5.2 kg
Packaging content	
Stand included	Yes
Cables included	AC, HDMI, USB Type-C to USB Type-C
Quick start guide	Yes
Other features	
Hardware calibration	Yes
Warranty period	5 year(s)
Look-up table (LUT) bit depth	16
Compliance certificates	CB, CCC, CE, China Compulsory Certification (CCC), Federal Communications Commission (FCC), PSE, RoHS, cTUVus, UKCA, WEEE
Certification	CE, UKCA, CB, TÜV/GS, TÜV Ergonomie geprüft (einschließlich ISO 9241-307), RCM, cTÜVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, RoHS, WEEE, China RoHS, CCC
Logistics data	
Harmonized System (HS) code	85285210