

JUNG

Sensor Butonash KNX JUNG LS 5292 1ST, 2-funksional, 4 Pika Komandimi, Matje Temperature, LED Statusi, KNX Secure, F50

SKU: 21003830 · EAN: 4011377321328

SPECIFIKAT TEKNIKE	
21 specifikat e produktit	
ATRIBUTI	VLERA
Network	
Bus system	KNX TP
Features	
Mounting type	Flush-mounted (Unterputz), DIN 49073
Number of buttons (Tasten)	2
Number of actuation points	4
Bus coupling	Integrated
Anti-theft/dismantling protection	Yes
LED indication	Yes (per button, red/green/blue, configurable)
Display	No
Label field	No
Room temperature measurement	Yes
Extension module connection	Yes (1-4-fold, Art. LS 509.. TSEM)
Energy saving mode	Yes
KNX Data Secure	Compatible from ETS 5.7.7 / ETS 6.1.0
KNX functions	Switching, dimming, blind control, value transmitter, scene recall
Technical details	
IP rating	IP20
Material	Plastic
Min. installation box depth	25 mm
Country of origin	DE
Power	
Power consumption	0.288 W
Logistics data	
Weight	0.04 kg

Design

Compatible series

LS 1912, LS 990, LS Cube, LS Design, LS Plus, LS Zero