ELO TOUCH SYSTEMS

Digital Signage Elo 3204L, 32", Full HD, TFT-LCD, 400 nits, Touch PCAP, 2× HDMI, DP, USB-C - Zezë

SKU: 16011432 · EAN: 0843173156040

SPECIFIKAT TEKNIKE

59 specifikat e produktit

ATRIBUTI	VLERA
Display	
Panel type	TFT-LCD
Display diagonal	80 cm (31.5")
Display technology	LED
Display resolution	1920 x 1080 pixels
Display brightness	400 cd/m²
HD type	Full HD
Feature	Touchscreen
Number of simultaneous touchpoints	40
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	3000:1
Viewing angle. horizontal	178°
Viewing angle. vertical	178°
Display number of colours	16.7 million colours
Maximum frame rate	60 fps
Ports & interfaces	
HDMI ports quantity	2
HDMI version	1.4
DisplayPorts quantity	1
DisplayPort version	1.2
Feature	USB port
USB connector type	USB Type-C
Ethernet LAN (RJ-45) ports	2
Feature	RS-232 interface
Audio	
Feature	Built-in speaker(s)

Number of built-in speakers	2
RMS rated power	5 W
Design	
Product design	Kiosk design
Placement supported	Indoor
Orientation	Horizontal
Product colour	Black
Screen shape	Flat
Feature	VESA mounting
Panel mounting interface	400 x 400 mm
Performance	
Purpose	Universal
Feature	On Screen Display (OSD)
Mean time between failures (MTBF)	50000 h
Power	
Power consumption (typical)	45 W
Power consumption (standby)	2.3 W
Power consumption (off)	0.29 W
Energy efficiency class (SDR)	G
Energy consumption (SDR) per 1000 hours	29 kWh
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Energy efficiency scale	A to G
Weight & dimensions	
Display width	763.7 mm
Display depth	49.6 mm
Display height	458.1 mm
Display weight	10.9 kg
Packaging data	
Package width	905 mm
Package depth	160 mm
Package height	680 mm
Package weight	15.3 kg
Packaging content	
Cables included	AC

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 80%
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	10 - 95%
Certificates	
Certification	FCC
Network	
Feature	Ethernet LAN