

ABL

Stacion Karikimi ABL eM4 Twin Extender, 2x Type 2, 2x 11 kW ose 1x 22 kW, Matës Energjie MID, IP55, IK10 - Zezë

SKU: 99056459 · EAN: 4011721189789

SPECIFIKAT TEKNIKE**47 specifikat e produktit**

ATRIBUTI	VLERA
Design	
Model	eM4 Twin Extender, eichrechtskonform
Color	Black
Housing material	Plastic
Performance	
Rated power input	22 kW (3-phase)
Input voltage	230-400 V
Rated frequency	50 Hz
Number of charging points	2
Max. power per charging point	22 kW
Max. charging power (3-phase)	2 x 11 kW or 1 x 22 kW
Max. charging power (1-phase)	2 x 3.7 kW or 1 x 7.4 kW
Max charging current	32 A
Charging current range	6-32 A (1 A increment)
Ports & interfaces	
Charging socket type	Type 2 (IEC 62196-2), lockable, x2
Cable cross-section	2.5-10 mm ²
Network	
Connectivity	LAN, WLAN
OCPP version	1.6
Plug & Charge	Yes (ISO 15118)
Features	
RFID card reader	Yes
MID-compliant energy meter	Yes (eichrechtskonform)
DC fault current detection	Yes (≥ 6 mA)
RCCB type	Type A, 30 mA
Weld detection	Yes

Static load management	Yes
Dynamic load management	Yes
App configuration	Yes (Android and iOS)
Linkable as extender	Yes
Linkable via LAN	Yes
Linkable via WLAN	Yes
Technical details	
Operating temperature	-25 to 50 °C
Storage temperature	-30 to 75 °C
Relative humidity	5-95%, non-condensing
Pollution degree	3
Overvoltage category	III
Max. installation altitude	2000 m a.s.l.
Standby power loss	8 W
Upstream fuse required	32 A (C characteristic)
Country of manufacture	Germany
Certificates	
Protection class (IP)	IP55
Impact resistance	IK10
Safety class	I
Weight & dimensions	
Height	516 mm
Width	428 mm
Depth	145 mm
Net weight	10.5 kg
Packaging data	
Packaging dimensions (H x W x D)	581 x 503 x 230 mm
Packaging weight	approx. 13 kg
Mounting	
Mounting type	Wall mounting