

LINDY

Adapter për telefon Lindy 73413 / USB-A / Fast Charging / 18W - Bardhë

SKU: 26020626 · EAN: 4002888734134

SPECIFIKAT TEKNIKE	
64 specifikat e produktit	
ATRIBUTI	VLERA
Performance	
Charger compatibility	Universal
Power source type	AC
USB 2.0 ports quantity	1
USB Type-C ports quantity	1
Feature	Fast charging
Fast charging technology	Adaptive Fast Charging, Power Delivery
Sockets quantity	2
Socket type	Type C (Europlug)
Charger type	Indoor
Number of outputs	2 outputs
Feature	USB Power Delivery (USB PD)
USB Power Delivery up to	20 W
Power protection features	Over current, Over voltage, Overheating, Short circuit
Design	
Product colour	White
Housing material	Acrylonitrile butadiene styrene (ABS), Polycarbonate (PC)
Connector material	Copper
Housing material	ABS (Acrylonitrile butadiene styrene), PC (Polycarbonate)
Power	
Input voltage	100 - 240 V
Input frequency	50 - 60 Hz
Input current	0.4 A
Maximum output voltage	12 V
Minimum output voltage	5 V
Output voltage accuracy (±)	5%
AC adapter power	20 W

AC adapter output current	3 A
Port 1 output power	18 W
Port 2 output power	20 W
Output current (5V)	3 A
Output current (9V)	2 A
Output current (12V)	1.5 A
Power consumption (no load)	0.1 W
Average active efficiency	5V 81.39%, 9V 85.48%, 12V 85.48%
Feature	Efficiency at low load (10%)
Power plug type	Type C
Port 1 (USB-A) output power	18 W
Port 2 (USB-C) output power	20 W
Fast charging technology	Adaptive Fast Charging, Power Delivery (USB PD)
Output voltage	5 - 12 V
Power plug type	Type C (Europlug)
Weight & dimensions	
Width	42.6 mm
Depth	28.8 mm
Height	41 mm
Weight	50 g
Packaging data	
Package width	81 mm
Package depth	31.5 mm
Package height	120 mm
Package weight	75 g
Package type	Carton
Operational conditions	
Operating temperature (T-T)	0 - 25 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	0 - 70%
Storage relative humidity (H-H)	0 - 80%
Operating temperature	0 - 25 °C
Storage temperature	-20 - 70 °C
Operating relative humidity	0 - 70%
Storage relative humidity	0 - 80%

Packaging content	
Feature	AC adapter included
Feature	Manual
AC adapter included	Yes
Manual included	Yes
Certificates	
Compliance certificates	CE, REACH, RoHS
Ports & interfaces	
USB Type-A ports	1 x USB 2.0
USB Type-C ports	1 x USB-C
Features	
Power protection	Over current, Over voltage, Overheating, Short circuit