LANCOM

Switch LANCOM GS-3652XP, 36× Gigabit Ethernet RJ45, 12× 2.5GbE RJ45, 4× SFP+ 10G, Layer 3 Lite Managed, 740W PoE+, 212Gbps - Zezë

SKU: 26029306 · EAN: 4044144618789

SPECIFIKAT TEKNIKE

71 specifikat e produktit

ATRIBUTI	VLERA
Management features	
Switch type	Managed
Switch layer	L3
Feature	Quality of Service (QoS) support
Feature	Web-based management
Feature	Configuring Location Settings (CLI)
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	48
Basic switching RJ-45 Ethernet ports type	2.5G Ethernet (100/1000/2500)
Gigabit Ethernet (copper) ports quantity	36
2.5G Ethernet (copper) ports quantity	12
SFP+ module slots quantity	4
Console port	RJ-45
Power connector	AC-in jack
Network	
Feature	10G support
Feature	Port mirroring
Feature	Flow control support
Feature	Link aggregation
Feature	Broadcast storm control
Feature	Spanning tree protocol
Feature	Cable length detection
Virtual LAN features	IP subnet–based VLAN, MAC address-based VLAN, MVRP, Private VLAN, Tagged VLAN, Voice VLAN
Number of VLANs	4093
Data transmission	

Switching capacity	212 Gbit/s
Throughput	130 Mpps
MAC address table	32000 entries
Feature	Store-and-forward
Feature	Static route
Feature	Jumbo frames support
Jumbo frames	10240
Packet buffer memory	4 MB
Security	
DHCP features	DHCP Option 66, DHCP Option 67, DHCP Option 82, DHCP client, DHCP relay, DHCP server, DHCP snooping
Feature	Access Control List (ACL)
Feature	IGMP snooping
Feature	IGMP proxy
Feature	SSH/SSL support
Authentication type	RADIUS, TACACS+
Multicast features	
Feature	Multicast support
Multicast Listener Discovery (MLD) snooping	Y
Protocols	
Feature	GARP VLAN Registration Protocol (GVRP)
Feature	IP Source Guard (IPSG)
Design	
Feature	Rack mounting
Form factor	1U
Product colour	Black
Housing material	Metal
Feature	Reset button
Number of fans	1 fan(s)
Performance	
Noise level	50 dB
Feature	Firmware upgradeable
Power	
Power source	AC/PoE
Feature	Power supply included
AC input voltage	100 - 240 V

AC input frequency	50/60 Hz
Power consumption (max)	870 W
Power over Ethernet (PoE)	
Feature	Power over Ethernet (PoE)
Total Power over Ethernet (PoE) budget	740 W
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 90%
Heat dissipation	444 BTU/h
Weight & dimensions	
Width	442 mm
Depth	375 mm
Height	44 mm
Weight	5.5 kg
Packaging content	
Cables included	AC, Serial
Feature	Quick start guide
Packaging data	
Feature	Mounting brackets included
Package width	470 mm
Package depth	534 mm
Package height	100 mm
Package weight	6.16 kg
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC)
Logistics data	
Customs product code (TARIC)	85176200
Country of origin	Taiwan