ONLINE USV-SYSTEME

UPS ONLINE USV-Systeme XANTO 2000, 2000VA, 2000W, Online, 230V, 8x IEC C13 - Zezë

SKU: 99057475 · EAN: 4026908003697

SPECIFIKAT TEKNIKE

50 specifikat e produktit

ATRIBUTI	VLERA
Features	
UPS topology	Double-conversion (Online)
Output power capacity	2 kVA
Output power	2000 W
Waveform	Sine
Input operation voltage (min)	110 V
Input operation voltage (max)	300 V
Input frequency	50/60 Hz
Output operation voltage (min)	208 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Maximum current	15.3 A
Efficiency	97%
Feature	Emergency Power Off (EPO)
Noise level	50 dB
Surge protection features	Fax, Modem, Network
Feature	Audible alarm(s)
Management protocols	SNMP
Audible alarm modes	Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	C13 coupler
Power plug	C20 coupler
AC outlets quantity	8 AC outlet(s)
Feature	USB port
USB 2.0 ports quantity	1
Feature	Serial interface
Serial interface type	RS-232

Serial ports quantity	1
RS-232 ports	1
Battery	
Battery capacity	9 Ah
Battery voltage	12 V
Number of batteries supported	4
Typical backup time at full load	6 min
Typical backup time at half load	16 min
Battery recharge time	4 h
Feature	Cold start
Design	
Form factor	Tower
Cooling type	Active
Product colour	Black
Display type	LCD
International Protection (IP) code	IP20
Mean time between failures (MTBF)	50000 h
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 90%
Certificates	
Certification	VFI-SS-111 (EN62040-3)EN62040-1EN62040-2CE
Packaging content	
Cables included	Input power cable, Power load cable, USB cable
Weight & dimensions	
Width	190 mm
Depth	415 mm
Height	335 mm
Weight	20.3 kg
Packaging data	
Package type	Box
Logistics data	
Harmonized System (HS) code	85078000