CISCO

Telefon Konference VoIP Cisco 8832, Ekran 3.9", Wi-Fi, USB-C - Hiri

SKU: 26033115 · EAN: 0889728126205

SPECIFIKAT TEKNIKE

38 specifikat e produktit

ATRIBUTI	VLERA
Features	
Product type	IP conference phone
Suitable for room area up to	74.3 m²
Control type	Buttons
Product colour	Charcoal
Feature	Built-in display
Display type	LCD
Display diagonal	9.91 cm (3.9")
Display resolution	480 x 128 pixels
Voice codecs	G.711a, G.711u, G.722, G.729A, G.729ab, OPUS, iLBC
Frequency range	100 - 20000 Hz
Feature	Noise reduction
Feature	Microphone mute
Ethernet interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Feature	Power over Ethernet (PoE)
Supported network protocols	IPv4, IPv6, SIP, SDP, UDP, DHCP, GARP, TFTP, HTTPS, RTP, RTCP, Cisco Discovery Protocol, LLDP
Security algorithms	EAP-FAST, EAP-TLS, SHA-256, SSH
Feature	Conference call
Feature	Call forwarding
Feature	Call hold
Feature	Call waiting
Feature	Call transfer
Certification	CE, UL, CSA
Call management	
Feature	Speed dialling

Ports & interfaces	
RJ-45 ports quantity	1
Feature	USB port
USB connector type	USB Type-C
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-10 - 60 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 95%
Weight & dimensions	
Width	278 mm
Depth	278 mm
Height	61 mm
Weight	1.85 kg
Packaging content	
Cables included	USB
Feature	AC adapter included
Logistics data	
Harmonized System (HS) code	85176990