

LEVEL ONE

Switch Industrial LevelOne IGS-2108, 8 porta Gigabit Ethernet, Smart Managed, Switching Capacity 16Gbps, IP30, DIN-Rail - Zezë

SKU: 26030937 · EAN: 4015867236185

SPECIFIKAT TEKNIKE

78 specifikat e produktit

ATRIBUTI	VLERA
Management features	
Switch type	Managed
Switch layer	L2
Feature	Quality of Service (QoS) support
Feature	Web-based management
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Gigabit Ethernet (copper) ports quantity	8
Network	
Networking standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Feature	Port mirroring
Feature	Full duplex
Feature	Half duplex
Feature	Flow control support
Feature	Link aggregation
Feature	Broadcast storm control
Feature	Rate limiting
Feature	Auto MDI/MDI-X
Feature	Spanning tree protocol
Feature	Auto-negotiation
Feature	MAC address auto-learning supported
Feature	MAC address auto-aging supported
Feature	VLAN support

Virtual LAN features	Port-based VLAN, Tagged VLAN
Number of VLANs	32
Data transmission	
Switching capacity	16 Gbit/s
Forwarding rate	11.904 Mpps
MAC address table	4000 entries
Feature	Jumbo frames support
Jumbo frames	9000
Packet buffer memory	1.5 MB
Security	
Feature	IGMP snooping
Queue scheduling algorithms	Priority queuing (PQ)
Multicast features	
Feature	Multicast support
Design	
Product colour	Black
LED indicators	Activity, Link, Power
International Protection (IP) code	IP30
Feature	DIN rail mounting
Performance	
Flash memory	2 MB
Noise level	0 dB
Feature	Fanless
Mean time between failures (MTBF)	43800 h
Power	
Power source	DC
Feature	Redundant power supply (RPS) support
DC input voltage	12 - 57 V
Power consumption (typical)	6 W
Feature	Surge protection
Surge protection voltage	4 kV
Power protection features	Surge protection
Operational conditions	
Operating temperature (T-T)	-40 - 75 °C
Storage temperature (T-T)	-40 - 85 °C

Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 95%
Heat dissipation	20.47 BTU/h
Weight & dimensions	
Width	153 mm
Depth	114 mm
Height	38 mm
Weight	530 g
Packaging content	
Feature	Quick start guide
Packaging data	
Feature	Terminal block included
Package type	Box
Feature	DIN rail included
Package width	230 mm
Package depth	160 mm
Package height	73 mm
Package weight	780 g
Sustainability	
Feature	Sustainability compliance
Technical details	
Layers per pallet (air)	16 pc(s)
Pallet gross length	80 cm
Pallet gross width	120 cm
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), RoHS, UKCA
Logistics data	
Pallet gross height	154.4 cm
Country of origin	China
Master (outer) case width	480 mm
Master (outer) case length	395 mm
Master (outer) case height	350 mm
Harmonized System (HS) code	8517620090
Master (outer) case gross weight	16 kg
Products per master (outer) case	20 pc(s)