

LG

Digital Signage LG 43UL3Q-E, 43", 4K UHD, ADS, 60Hz, 8GB, 3× HDMI, 2× USB-A - Zezë

SKU: 16011525 · EAN: 8806096497524

SPECIFIKAT TEKNIKE	
73 specifikat e produktit	
ATRIBUTI	VLERA
Display	
Panel type	ADS
Display diagonal	109.2 cm (43")
Display technology	LED
Display resolution	3840 x 2160 pixels
Display brightness	350 cd/m²
HD type	4K Ultra HD
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	1200:1
Contrast ratio (dynamic)	1000000:1
Viewing angle. horizontal	178°
Viewing angle. vertical	178°
Display number of colours	1.07 billion colours
Colour saturation	80%
Rated lifetime	30000 h
Native refresh rate	60 Hz
Haze rate	1%
Ports & interfaces	
HDMI ports quantity	3
HDMI version	2.2/1.4
Feature	USB port
Ethernet LAN (RJ-45) ports	1
Feature	RS-232C
Feature	PC Audio out
Audio	
Feature	Built-in speaker(s)

Number of built-in speakers	2
RMS rated power	20 W
Design	
Product design	Digital signage flat panel
Placement supported	Indoor
Orientation	Horizontal/Vertical
Product colour	Black
Feature	VESA mounting
Panel mounting interface	200 x 200 mm
Bezel width (bottom)	1.08 cm
Bezel width (side)	1.08 cm
Bezel width (top)	1.08 cm
Bezel colour	Black
Performance	
Purpose	Commercial
Operating hours (hours/days)	16/7
Feature	Web browser
Feature	webRTC support
Power	
Power consumption (typical)	83 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.5 W
Power consumption (max)	134 W
Power consumption (economy mode)	0.5 W
Energy efficiency class (SDR)	G
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	82.5 kWh
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Heat generation (typical)	283.208 BTU/h
Heat generation (max)	457.227 BTU/h
Computer system	
Internal memory	8 GB
Operating system installed	WebOS
Operating system version	6.1

Weight & dimensions	
Display width	965 mm
Display depth	59.1 mm
Display height	554.9 mm
Display weight	7.6 kg
Packaging data	
Package width	1070 mm
Package depth	645 mm
Package height	113 mm
Package weight	9.7 kg
Packaging content	
Feature	Remote control included
Cables included	Power
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 80%
Sensors	
Feature	Gyroscope
Feature	Temperature sensor
Network	
Feature	Ethernet LAN
Feature	Wi-Fi
Technical details	
Compliance certificates	CB, CE, Electromagnetic Compatibility (EMC), Federal Communications Commission (FCC)
Other features	
Power supply type	Internal