AXIS

Konvertues Video Analog në IP AXIS M7104, 4 Kanale, 4x BNC, H.264/H.265, PoE, RS-485/422, microSD - Bardhë

SKU: 26032555 · EAN: 7331021066397

SPECIFIKAT TEKNIKE

34 specifikat e produktit

ATRIBUTI	VLERA
Video	
Maximum video resolution	720 x 576 pixels
Maximum frame rate	30 fps
Video compression formats	AVC, H.264, H.265, HEVC, MPEG4
NTSC resolutions	720x480 pixels
PAL resolutions	720x576 pixels
Channels quantity	4 channels
Performance	
Internal memory	1024 MB
Flash memory	512 MB
Feature	Card reader integrated
Compatible memory cards	MicroSD (TransFlash), MicroSDHC, MicroSDXC
Feature	PTZ control
Image settings	Brightness, Color, Compression, Contrast, Mirroring, Privacy mask, Rotation, Sharpness
Design	
Product colour	White
LED indicators	Status
Feature	Wall mountable
Network	
Feature	Quality of Service (QoS) support
Feature	Power over Ethernet (PoE)
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T
Networking standards	IEEE 802.3af, IEEE 802.3at
Security	
Security algorithms	HTTPS
Feature	Video motion detection

Feature	IP address filtering
Feature	Active tampering alarm
Ports & interfaces	
BNC input ports	4
Ethernet LAN (RJ-45) ports	1
RS-485 ports	2
Power	
Power consumption (typical)	4.7 W
Weight & dimensions	
Width	187 mm
Height	37 mm
Weight	650 g
Packaging content	
Feature	Manual
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 65 °C
Operating relative humidity (H-H)	10 - 85%