AXIS

Kamerë Sigurie IP CCTV Axis Q6225-LE, 2MP, 6.91–214.69mm, 31× Zoom Optik, PTZ 360°, OptimizedIR 400m, Lightfinder 2.0, Forensic WDR, Audio, PoE 95W, MicroSD, IP66, IP68, IK10 - Gri

SKU: 26028970 · EAN: 7331021084612

SPECIFIKAT TEKNIKE

78 specifikat e produktit

ATRIBUTI	VLERA
Performance	
Type	IP security camera
Placement supported	Outdoor
Connectivity technology	Wired
Feature	PTZ control
Feature	Auto-tracking
Feature	Tour recording
Feature	Wide Dynamic Range (WDR)
Feature	Day/night mode
Feature	Infrared (IR) cut-off filter
Processor model	ARTPEC-7
Feature	Built-in processor
Number of languages	18
Design	
Form factor	Box
Mounting type	Wall
Product colour	Grey
Housing material	Aluminium
International Protection (IP) code	IP66, IP68
IK code	IK10
Camera	
Feature	Camera pan control
Feature	Camera tilt control
Minimum illumination	0.05 lx
Lens viewing angle. horizontal	63.8°

Lens viewing angle. vertical	37°
Tilt angle range	-90 - 90°
Tilt speed	150 °/sec
Pan speed	150 °/sec
Camera shutter speed	1/111000 - 1/2 s
Image sensor	
Optical sensor size	25.4 / 2 mm (1 / 2")
Feature	Progressive scan
Sensor type	CMOS
Lens system	
Feature	Zoom capability
Optical zoom	31x
Digital zoom	12x
Focal length range	6.91 - 214.64 mm
Feature	Auto focus
Maximum aperture number	4.6
Minimum aperture number	1.36
Night vision	
Feature	Night vision
Night vision distance	400 m
LED type	IR
Infra-red wavelength	850 nm
Video	
Maximum resolution	1920 x 1080 pixels
Video compression formats	H.264, H.265, M-JPEG
Feature	Video recording
Frame rate	50 fps
Feature	Video streaming
Feature	Privacy masking
Network	
Feature	Ethernet LAN
Ethernet interface type	Gigabit Ethernet
Networking standards	IEEE 802.1x, IEEE 802.3bt
Feature	Quality of Service (QoS) support
Storage	

Feature	Card reader integrated
Compatible memory cards	SD, SDHC, SDXC
Flash memory	512 MB
Internal memory	1024 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Security	
Feature	Password protection
Feature	Video motion detection
Feature	IP address filtering
Feature	HTTPS encryption
Feature	Pixel counter
Feature	Digest authentication
Feature	Network access storage (NAS)
Power	
Power source type	PoE
AC input voltage	100 - 240 V
Power consumption (typical)	25 W
Power consumption (max)	71 W
Operational conditions	
Operating temperature (T-T)	-50 - 55 °C
Storage temperature (T-T)	-40 - 65 °C
Operating relative humidity (H-H)	10 - 100%
Weight & dimensions	
Width	313 mm
Depth	210 mm
Height	330 mm
Weight	8.7 kg
Packaging content	
Number of cameras	1
Cables included	LAN (RJ-45)
Feature	Manual
Packaging content	Windows decoder 1-user license, IK10 bumper, High PoE Midspan 1-port