CISCO

Switch Industrial Cisco Catalyst IE3400, 8x Gigabit Ethernet RJ45, 2x Gigabit SFP, Layer 2 Managed, DIN-Rail - Zezë

SKU: 26030541 · EAN: 0889728223379

SPECIFIKAT TEKNIKE

50 specifikat e produktit

ATRIBUTI	VLERA
Management features	
Switch type	Managed
Switch layer	L2
Feature	Quality of Service (QoS) support
Feature	ARP inspection
Feature	System event log
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Fiber ports quantity	2
Fiber optic connector	SFP
Console port	Mini USB-B/RS-232
USB 2.0 ports quantity	3
Compatible memory cards	SD
Network	
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Feature	Link aggregation
Feature	Broadcast storm control
Feature	Spanning tree protocol
Feature	VLAN support
Number of VLANs	256
Data transmission	
MAC address table	8000 entries
Number of queues	8
Security	
DHCP features	DHCP snooping
Feature	Access Control List (ACL)

Access Control List (ACL) IPv4 entries	2000
Access Control List (ACL) IPv6 entries	512
Feature	IGMP snooping
IGMP entries	1000
Security algorithms	802.1x RADIUS, SNMPv3, SSH
Feature	MAC address filtering
Feature	BPDU filtering/protection
Authentication	Guest VLAN
Multicast features	
Feature	Multicast support
Design	
Feature	Rack mounting
Product colour	Black
International Protection (IP) code	IP20
Feature	DIN rail mounting
Performance	
Internal memory	4000 MB
Flash memory	1500 MB
Mean time between failures (MTBF)	549808 h
Power	
DC input voltage	9.6 - 60 V
Input current	6.3 A
Power consumption (typical)	36 W
Operational conditions	
Operating temperature (T-T)	-40 - 70 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	5 - 95%
Non-operating altitude	0 - 4572 m
Weight & dimensions	
Width	152.4 mm
Depth	134.6 mm
Height	91.4 mm
Weight	1.72 kg
Logistics data	
Harmonized System (HS) code	85176990