LIAN LI

Furnizues Energjie Lian Li RS1000G, 1000 W, ATX 3.1, 80 PLUS Gold, Full Modular - Zezë

SKU: 17018017 · EAN: 4718466019165

SPECIFIKAT TEKNIKE

51 specifikat e produktit

ATRIBUTI	VLERA
Specifikat	
Modeli	Lian Li RS1000G (RS1000G.W)
Fuqia totale	1000 W
Forma	ATX
Ngjyra	E bardhë
Efikasiteti	80 PLUS Gold, Cybenetics Platinum, PPLP Gold
Shpërndarje +12V	Single Rail, 83.3 A
Modulariteti	Plotësisht modular
Lidhëse CPU	2x EPS/ATX 12V
Lidhëse 12V-2x6 (native)	1
Lidhëse PCIe 6+2 pin	4
Lidhëse SATA	12
Hyrja AC	E rrotullueshme 90°
Dalje duale 24-pin	Po (dy anët)
RS Hub (USB)	Opsional (nuk përfshihet)
Dimensionet	150 x 150 x 86 mm
Technical details	
Standard	ATX 3.1, PCIe 5.1
Other features	
Fan	135 mm FDB, modalitet Zero RPM
Power	
Total power	1000 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Input current	8 - 15 A
Power Factor Correction (PFC) type	Active
Combined power (+3.3V)	100 W

Combined power (-12V)	1200 W
Combined power (+5V)	100 W
Combined power (+5Vsb)	100 W
Power protection features	No load operation, Over current, Over power, Over voltage, Short circuit, Surge & inrush protection (SIP), Under temperature, Under voltage
Ports & interfaces	
Motherboard power connector	20+4 pin ATX
Motherboard power cable length	62 cm
Peripheral (Molex) power connectors (4-pin)	4
Peripheral (Molex) power cable length	500 mm
PCI Express power connectors (6+2 pin)	2
PCI Express power cable length	65 cm
CPU power cable length	70 cm
Feature	ATX power connector (20+4 pin)
Cabling type	Fully-Modular
Performance	
80 PLUS certification	80 PLUS Gold
Purpose	PC
Power supply unit (PSU) form factor	ATX
ATX version	3.1
Noise level	36.21 dB
Bearing technology	FDB
Mean time between failures (MTBF)	100000 h
Design	
Product colour	White
Fan diameter	13.5 cm
Number of fans	1 fan(s)
Fan speed	0 - 1600 RPM
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Weight & dimensions	
Width	86 mm
Depth	150 mm
Height	150 mm