HIKVISION

# Kamerë Sigurie IP CCTV Hikvision Pro Series with ColorVu DS-2CD2H47G3-LIZS2UY/SL, 4MP, 2.8–12mm, ColorVu, Smart Hybrid Light, AcuSense, WDR 130 dB, PoE - Bardhë

SKU: 26026854 · EAN: 6936422158798

## SPECIFIKAT TEKNIKE

**20 specifikat e produktit**

| ATRIBUTI | VLERA |
|---|---|
| **Camera** | |
| Model | DS-2CD2H47G3-LIZS2UY/SL(2.8-12mm) |
| Resolution | 4 MP (2688x1520) |
| Image sensor | 1/1.8" Progressive Scan CMOS |
| Min. illumination | 0.0005 Lux (Color, F1.2, AGC ON), 0 Lux with light |
| **Lens system** | |
| Focal length | 2.8-12 mm motorized varifocal |
| Max. aperture | F1.2 |
| Horizontal FOV | 114.6° (wide) - 41.8° (tele) |
| **Night vision** | |
| Night vision range | 40 m (Smart Hybrid Light) |
| Night vision type | Smart Hybrid Light (IR + White Light) |
| **Features** | |
| Video analytics | AcuSense 3.0 (human/vehicle detection) |
| Image technology | ColorVu 3.0, HIKAI-ISP |
| **Audio** | |
| Built-in audio | Microphone + Speaker (siren/strobe deterrent) |
| **Security** | |
| Protection rating | IP67, IK10, NEMA 4X |
| **Power over Ethernet (PoE)** | |
| PoE standard | IEEE 802.3at, Class 4, max. 20 W |
| **Power** | |
| Power supply | 12 VDC ± 25%, max. 16.8 W |
| **Operational conditions** | |
| Operating temperature | -30°C to 60°C |

| | |
|---|---|
| Humidity | 95% or less (non-condensing) |
| **Weight & dimensions** | |
| Weight | approx. 1265 g |
| **Design** | |
| Camera type | Turret (Eyeball) |
| Series | EasyIP 4.0 (Pro Series) |