EATON

UPS Eaton 9PX1000IRT2U, 1000 VA, 1000 W, Online, 8 Priza IEC C13, Rack/Tower 2U – Zezë, Argjend

SKU: 99056112 · EAN: 0743172081407

SPECIFIKAT TEKNIKE

45 specifikat e produktit

ATRIBUTI	VLERA
Features	
UPS topology	Double-conversion (Online)
Output power capacity	1 kVA
Output power	1000 W
Waveform	Pure sine
Input operation voltage (min)	176 V
Input operation voltage (max)	276 V
Input frequency	40/70 Hz
Output operation voltage (min)	200 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Number of input phases	1
Efficiency	91.5%
Power factor	1
Noise level	35 dB
Power protection features	Battery discharge
Ports & interfaces	
AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	8 AC outlet(s)
Feature	USB port
USB 2.0 ports quantity	1
Feature	Serial interface
Serial interface type	RS-232
RS-232 ports	1
Battery	
Battery technology	Sealed Lead Acid (VRLA)

Typical backup time at full load	6 min
Typical backup time at half load	16.5 min
Feature	Hot-swap battery
Feature	Automatic battery test
Design	
Form factor	Rackmount/Tower
Rack capacity	2U
Product colour	Black
Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Certificates	
Certification	IEC/EN 62040-1, UL 1778, CSA 22.2, IEC/EN 62040 -2, FCC Class B, CISPR22 Class B, CE /CB report (TUV) / cULus / EAC /RCM / KC / Energy Star
Packaging content	
Feature	Rack mount kit
Safety regulation & standards	
Safety	IEC/EN 62040-1, UL 1778, CSA 22.2
Sustainability	
Sustainability certificates	ENERGY STAR
Weight & dimensions	
Width	440 mm
Depth	450 mm
Height	86.5 mm
Weight	19.5 kg
Packaging data	
Bundled software	Intelligent Power Software suite
Logistics data	
Harmonized System (HS) code	85078000
Other features	
Nominal input voltage	230 V