KEBA ENERGY AUTOMATION GMBH

Stacion Karikimi KEBA P30 x-series, 22 kW, Prizë Type 2, RFID, ISO 15118 Ready – Zezë

SKU: 99056455 · EAN: 9120050716353

SPECIFIKAT TEKNIKE

26 specifikat e produktit

ATRIBUTI	VLERA
Performance	
Charging power	22 kW
Charging mode	Mode 3 (IEC 61851-1)
AC phases	3-phase (1-phase / 3-phase switchable)
Rated voltage	3 x 230 V / 400 V AC, 50 Hz
Adjustable charging current	10 / 13 / 16 / 20 / 25 / 32 A
Ports & interfaces	
Charging connector	Type 2 socket (IEC 62196)
Ethernet	LSA+ terminals 10/100/1000 Mbit/s, RJ45
USB	Type A, USB 2.0, max. 500 mA
Network	
Connectivity	Wi-Fi (WLAN), Modbus TCP
Protocol	OCPP 1.5 / 1.6
Smart Home	UDP, Modbus TCP
Features	
Access control	RFID (MIFARE / ISO 14443 / ISO 15693)
ISO 15118 (Plug & Charge)	Hardware-ready
Energy meter	MID-certified
Load management	Hub (master for up to 15 P30 c-series units)
DC fault current detection	Yes
Offline session logging	Up to 3 months
PV surplus charging	Yes
Technical details	
Protection class	IP54
Impact resistance	IK10
Housing material	Plastic
Installation	Indoor / outdoor, wall or pole mount

Weight & dimensions	
Dimensions (H x W x D)	516 x 240 x 166 mm
Weight	5.0 kg
Design	
Colour	Green Edition
Certificates	
Energy meter certification	MID