HIKVISION

Kamera Sigurie IP CCTV Hikvision DS-2TD2617B-6/PA, 4MP, 2688 × 1520, 8mm, PoE, IP66 - Bardhë

SKU: 26025811 · EAN: 6941264046271

SPECIFIKAT TEKNIKE

70 specifikat e produktit

ATRIBUTI	VLERA
Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Feature	Wide Dynamic Range (WDR)
Feature	Day/night mode
Feature	Alarm input/output
Number of languages	32
Languages support	Multi
Design	
Form factor	Bullet
Mounting type	Ceiling/wall
Product colour	White
International Protection (IP) code	IP66
Camera	
Minimum illumination	0.0018 lx
Lens viewing angle. horizontal	39.42°
Lens viewing angle. vertical	22.14°
White balance	ATW, Auto, Daylight, Indoor, Lamp, Manual, Outdoor, Sodium lamp
Camera shutter type	Electronic
Camera shutter speed	1 - 1/100000 s
Adjustment shutter speed	Auto/Manual
Image sensor	
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")
Feature	Progressive scan
Sensor type	CMOS
Number of effective pixels (H x V)	2688 x 1520 pixels

Lens system	
Feature	Fixed focus
Maximum aperture number	1.1
Fixed focal length	8 mm
Night vision	
Feature	Night vision
Night vision distance	40 m
LED type	IR
Video	
Maximum resolution	2688 x 1520 pixels
Total megapixels	4 MP
Video compression formats	H.264, H.265, MPEG
Supported graphics resolutions	176 x 144, 320 x 240, 352 x 288, 384 x 288, 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2688 x 1520
Supported video modes	240p, 360p, 480p, 540p, 576p, 720p, 768p, 1080p, 1440p, 1520p
Frame rate	30 fps
Feature	Video streaming
Feature	Noise reduction
Noise reduction technology	3D noise reduction
Audio	
Audio input channels	1.0 channels
Audio formats supported	G.711, G.711 A-law, G.711 ;ÂÖÆ w, G.726, MP2L2, PCM
Network	
Feature	Ethernet LAN
Ethernet interface type	Fast Ethernet
Networking standards	IEEE 802.1x, IEEE 802.3af
Supported network protocols	IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE
Number of users	32 user(s)
Feature	Quality of Service (QoS) support
Storage	
Feature	Card reader integrated
Compatible memory cards	MicroSD (TransFlash), MicroSDHC, MicroSDXC
Maximum memory card size	128 GB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1

RS-485 ports	1
Feature	Microphone in
Feature	DC-in jack
Security	
Feature	IP address filtering
Feature	HTTPS encryption
Management features	
Feature	Web browser
Feature	Reset button
Power	
Power source type	DC, PoE
Power consumption (max)	7.5 W
Power consumption (Power over Ethernet (PoE))	8 W
DC output voltage	12
Operational conditions	
Operating temperature (T-T)	10 - 35 °C
Operating relative humidity (H-H)	0 - 95%
Weight & dimensions	
Width	113.5 mm
Height	115.2 mm
Length	358.3 mm
Weight	1.76 kg
Packaging data	
Package type	Box
Packaging content	
Number of cameras	1
Cables included	LAN (RJ-45)