EATON

UPS Eaton 5P850IRG2, 850 VA, 680 W, Line-Interactive, 4 Priza IEC C13, Rack 1U – Zezë

SKU: 99056114 · EAN: 3553340710308

SPECIFIKAT TEKNIKE

42 specifikat e produktit

ATRIBUTI	VLERA
Design	
Form factor	Rack 1U
Construction type	482.6 mm (19 inch)
Color	Black/Silver
Performance	
Topology	Line-interactive
VA rating	850 VA
Wattage	680 W
Output waveform	Sine wave
Efficiency	up to 98%
Auto shutdown function	Yes
Power	
Input connection	C14
Input voltage range	160-294 V (adjustable to 150-294 V)
Input frequency range	47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system)
Nominal input current	4.1 A
Output voltage	230 V default (200/208/220/230/240 V)
Output receptacles	(4) C13
Outlet groups	2 programmable
Battery	
Battery type	Lead-acid maintenance-free (replaceable)
Battery rating	6 V / 7 Ah
Battery quantity	4
Battery management	ABM+ (ABM or constant voltage, user selectable), automatic test, deep discharge protection
Hot swappable batteries	Yes
Runtime at 50% load	13 min

Runtime at 70% load	8 min
Runtime at 100% load	3 min
Display	
User interface	Multilingual graphical LCD display
Ports & interfaces	
USB port	Yes (HID compliant)
Serial port	RS-232
Communication slot	1 slot for optional card (Network management, Relay, or Network and Industrial card)
Remote On/Off	Yes (mini-terminal block)
Operational conditions	
Temperature range	0-40°C
Relative humidity	0-90% non-condensing
Altitude	3000 m
Noise level	<35 dB at 1 m
BTU rating	Online: 46 BTU/hr, Battery: 307 BTU/hr
Weight & dimensions	
Product depth	509 mm
Product width	438 mm
Product height	43.2 mm
Product weight	13.7 kg
Packaging content	
Package contents	Rack-mounting kit, Cable locking system, USB cable, (2) IEC-IEC cables, Quickstart guide, Safety instructions
Certificates	
Certifications	IEC/EN 62040-1, IEC/EN 62040-2, IEC/EN 62040-3, UL 1778, CSA-C22.2, CE, UKCA
Compliances	LVD Directive, EMC Directive, RoHS, WEEE, Packaging Directive, Batteries Directive
Software	
Software compatibility	Eaton Brightlayer Software suite