CISCO

# Switch Cisco Catalyst C9200L-48T-4G-E, 48x Gigabit Ethernet RJ45, 4x Gigabit SFP, Network Essentials, Layer 3 Managed, Rackmount 1U - Hiri

SKU: 26030237 · EAN: 0889728170147

## SPECIFIKAT TEKNIKE

### 54 specifikat e produktit

| ATRIBUTI | VLERA |
|---|---|
| **Management features** | |
| Switch type | Managed |
| Switch layer | L3 |
| Feature | Quality of Service (QoS) support |
| Feature | Web-based management |
| Feature | Traffic classification |
| Feature | ARP inspection |
| Feature | Configuring Location Settings (CLI) |
| **Ports & interfaces** | |
| Basic switching RJ-45 Ethernet ports quantity | 48 |
| Basic switching RJ-45 Ethernet ports type | Gigabit Ethernet (10/100/1000) |
| Gigabit Ethernet (copper) ports quantity | 4 |
| Power connector | AC-in jack |
| **Network** | |
| Feature | 10G support |
| Copper ethernet cabling technology | 10BASE-T, 10GBASE-T, 100BASE-TX, 1000BASE-T |
| Feature | Full duplex |
| Feature | IP routing |
| Routing entries | 3000 |
| Feature | Flow control support |
| Feature | Spanning tree protocol |
| Feature | VLAN support |
| Number of VLANs | 4096 |
| **Data transmission** | |
| Switching capacity | 104 Gbit/s |
| Forwarding rate | 77.38 Mpps |

| | |
|---|---|
| MAC address table | 16000 entries |
| Feature | Jumbo frames support |
| Jumbo frames | 9198 |
| Packet buffer memory | 6 MB |
| **Security** | |
| Feature | Access Control List (ACL) |
| Security algorithms | 128-bit AES |
| **Multicast features** | |
| Feature | Multicast support |
| Multicast MAC address table | 1000 entries |
| IPv4 multicast entries | 3000 |
| IPv6 multicast entries | 1500 |
| **Protocols** | |
| Management protocols | SNMPv1/v2c/v3 |
| Routing protocols | CDP, EIGRP, OSPF, RIP, VRRP |
| **Design** | |
| Product colour | Grey |
| **Performance** | |
| Memory type | DRAM |
| Internal memory | 2000 MB |
| Flash memory | 4000 MB |
| **Power** | |
| Feature | Power supply included |
| Feature | Redundant power supply (RPS) support |
| AC input voltage | 100 - 240 V |
| AC input frequency | 50 - 60 Hz |
| Input current | 1.6 - 0.7 A |
| Power consumption (typical) | 125 W |
| **Operational conditions** | |
| Operating temperature (T-T) | -5 - 45 °C |
| Storage temperature (T-T) | -40 - 70 °C |
| Operating relative humidity (H-H) | 5 - 90% |
| Operating altitude | 0 - 3000 m |
| **Weight & dimensions** | |
| Width | 445 mm |

| | |
|---|---|
| Depth | 288 mm |
| Height | 44 mm |
| **Packaging data** | |
| Package type | Box |
| **Certificates** | |
| Certification | RoHS, IEC 60950-1, UL 60950-1, CAN/CSA C22.2 No. 60950-1, EN 60950-1, AS/NZS 60950.1 |
| **Logistics data** | |
| Harmonized System (HS) code | 85176990 |