

ASUSTOR

NAS ASUSTOR Lockerstor 10 AS6510T, 10 Bay, Intel Atom C3538, 8GB DDR4, 2 × 10GbE, 2 × 2.5GbE, 2 × M.2 NVMe - Zezë

SKU: 26031703 · EAN: 4710474831227

SPECIFIKAT TEKNIKE

125 specifikat e produktit

ATRIBUTI	VLERA
Storage	
Storage drive capacity	0 GB
Supported storage drive interfaces	Serial ATA III
Storage drive sizes supported	2.5,3.5,M.2
Number of M.2 (M & B) slots	2
Feature	RAID support
RAID levels	0, 1, 5, 6, 10, JBOD
Feature	Online RAID migration
Feature	Online RAID expansion
Supported file systems	BTRFS, FAT32, HFS+, NTFS, exFAT, ext3, ext4
Total installed storage capacity	0 TB
Number of storage drives supported	10
Installed storage drive type	No
Supported storage drive types	HDD & SSD
Feature	Bad block scan
Processor	
Processor manufacturer	Intel
Processor family	Intel Atom®
Processor model	C3538
Processor frequency	2.1 GHz
Processor cores	4
Processor threads	4
Processor cache	8 MB
CPU configuration (max)	1
PCI Express slots version	3.0
Processor cache type	Smart Cache

Processor code	SR3L7
Processor codename	Denverton
Processor lithography	14 nm
Processor operating modes	64-bit
Processor package size	34 x 28 mm
Processor socket	BGA 1310
Stepping	B1
Tcase	87 °C
Tjunction	100 °C
Thermal Design Power (TDP)	15 W
Maximum internal memory supported by processor	256 GB
Feature	Conflict-Free processor
Memory	
Internal memory	8 GB
Internal memory type	DDR4
Memory clock speed	2133 MHz
Maximum RAM supported	64 GB
Memory slots	2
Memory form factor	SO-DIMM
Flash memory	4096 MB
Network	
Feature	Ethernet LAN
Ethernet LAN data rates	100,1000,2500,10000 Mbit/s
Ethernet LAN data rate supported (max)	10000 Mbit/s
Feature	DHCP server
Feature	Jumbo frames support
Feature	iSCSI support
Feature	Wake-on-LAN ready
Supported network protocols	TCP/IP (IPv4 & IPv6), CIFS / SMB, SMB 2.0 / 3.0, AFP, NFS, FTP, TFTP, WebDAV, Rsync, SSH, SFTP, iSCSI/IP-SAN, HTTP, HTTPS, Proxy, SNMP
Feature	Link aggregation
Feature	Load balancing system
Feature	Dynamic DNS (DDNS)
Feature	WLAN adapter supported
Ports & interfaces	
Feature	USB port

USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
Ethernet LAN (RJ-45) ports	4
Design	
Chassis type	Tower
Cooling type	Active
Product colour	Black
Number of fans	2 fan(s)
Fan diameter	12 cm
Feature	Built-in display
Display type	LCD
Performance	
Type	NAS
Device class	Home & Home Office
Feature	Backup function
Backup features	Cloud, iSCSI LUN
Feature	Multilingual support
Number of users	4096 user(s)
Noise level (idle)	22 dB
Feature	Snapshot
Feature	Web-based management
Feature	Share folder access right management
Security algorithms	256-bit AES, HTTPS, SSH, SSL/TLS
Feature	Access Control List (ACL)
Feature	Reset button
Feature	Built-in UPnP AV media server
Feature	Built-in iTunes server
Browser supported	Internet Explore 11+, FireFox, Chrome, Safari, Microsoft Edge
Feature	System log
Feature	Disk scan
Feature	S.M.A.R.T. support
Share folder	Windows ACL
Feature	Universal Plug and Play (UPnP)
Software	
Operating system installed	ADM
Operating system version	3.4
Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows Vista, Windows XP

Linux operating systems supported	Yes
Mac operating systems supported	Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey
Server operating systems supported	Windows Server 2003, Windows Server 2008, Windows Server 2012
Other operating systems supported	Linux
Power	
Power supply location	Built-in
Power supply unit (PSU) capacity	250 W
Number of power supply units	1
Power consumption (typical)	76.8 W
Power consumption (HDD standby)	41.1 W
AC input voltage	100 - 240 V
Weight & dimensions	
Width	293 mm
Depth	230 mm
Height	215.5 mm
Weight	6.4 kg
Packaging content	
Cables included	AC, LAN (RJ-45)
Number of screws	66
Processor special features	
Feature	Embedded options available
Feature	Execute Disable Bit
Feature	Intel QuickAssist Technology
Feature	Intel Secure Boot
Intel Secure Boot Technology version	1.00
Intel Secure Key Technology version	1.00
Feature	Intel Virtualization Technology (VT-x)
Feature	Intel Virtualization Technology for Directed I/O (VT-d)
Feature	Intel VT-x with Extended Page Tables (EPT)
Feature	Intel® AES New Instructions (Intel® AES-NI)
Feature	Intel® OS Guard
Feature	Intel® Secure Key
Intel® Turbo Boost Technology	No
Maximum number of PCI Express lanes	12
Memory types supported by processor	DDR4-SDRAM

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	5 - 95%
Logistics data	
Harmonized System (HS) code	84714100
Other features	
Certification	FCC, CE, VCCI, BSMI, C-TICK
Processor ARK ID	97929