EPSON

Skaner EPSON WorkForce DS-900WN A4 Network & Wi-Fi / 70ppm /140ipm Feeder /100 faqe

SKU: 19011427 · EAN: 8715946734163

SPECIFIKAT TEKNIKE

62 specifikat e produktit

ATRIBUTI	VLERA
Scanning	
Maximum scan size	215.9 x 6096 mm
Optical scanning resolution	600 x 600 DPI
Colour scanning	Yes
Duplex scanning	Yes
Input colour depth	30 bit
Output colour depth	24 bit
Input greyscale depth	10 bit
Output greyscale depth	8 bit
ADF scan speed (b/w. A4)	70 ppm
ADF scan speed (colour. A4)	70 ppm
Duplex ADF scan speed (b/w. A4)	140 ipm
Duplex ADF scan speed (colour. A4)	140 ipm
Design	
Scanner type	Sheet-fed scanner
Product colour	White
Display	LCD
Display diagonal	10.7 cm (4.2")
Touchscreen	Yes
Control type	Touch
Built-in display	Yes
Performance	
Scan file formats	BMP, JPEG, PDF, PNG, TIFF
Daily duty cycle (max)	11000 pages
Built-in OCR	Yes
Scan to	Cloud, E-mail, Network folder, PC, USB
Scan drivers	ICA, ISIS, SANE, TWAIN, WIA

Barcode reader	Yes
Ultrasonic sensor	Yes
Scanner smart software features	Skip blank page function
Input capacity	
Standard input capacity	100 sheets
Auto document feeder (ADF) input capacity	100 sheets
Paper handling	
Scanning media types supported	Business Card, Envelopes, Plastic Card
Maximum ISO A-series paper size	A4
ISO A-series sizes (A0...A9)	A3, A4, A5, A6
ISO B-series sizes (B0...B9)	B4, B5, B6
Letter	Yes
Legal	Yes
Auto Document Feeder (ADF) media weight	27 - 413 g/m²
Ports & interfaces	
USB port	Yes
USB version	3.2 Gen 1 (3.1 Gen 1)
Network	
Wi-Fi	Yes
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Ethernet LAN	Yes
Power	
Power supply type	AC
Power consumption (typical)	19 W
Power consumption (standby)	1.2 W
Power consumption (PowerSave)	5.6 W
AC input frequency	50 - 60 Hz
Input voltage	100 - 240 V
Weight & dimensions	
Width	296 mm
Depth	212 mm
Height	217 mm
Weight	3.7 kg
Packaging data	
Quantity per pack	1 pc(s)

Packaging content	
Bundled software	Document Capture Pro, Epson Scan 2
Packaging content	Paper Alignment Plate, Carrier Sheet, Cleaning Kit
System requirements	
Windows operating systems supported	Yes
Mac operating systems supported	Yes
Linux operating systems supported	Yes
Operational conditions	
Operating temperature (T-T)	5 - 35 °C
Storage temperature (T-T)	-25 - 60 °C
Operating relative humidity (H-H)	15 - 80%
Storage relative humidity (H-H)	25 - 60%
Other features	
Warranty period	1 year(s)